

Lamartine Ltd.

FIREPLACE MANUFACTURERS
GRANITE KITCHEN WORKTOPS
STOVE & GAS FIRE STOCK LISTS



ROSE GREY RADIATOR

Accessories included: 2 stainless steel connection hoses, 1 infrared remote control (black or white).
3 metal frame colors available: white, gray, black
Option LED frame in warm white 3000K or neutral white 4000K

Dimensions: 190 x 54 cm - very thin: total thickness 11.5 cm

Heating power only:

Hot water (75/65/20 °C), V^③ 3740 W + V^② 2750 W + V^① 1700 W

Power Reversible hot & cold:

Hot water, low temperature (55/45/20 °C), V^③ 2170 W + V^② 1450 W + V^① 830 W

Chilled water, cold (7/12/27 °C), V^③ 1600 W + V^② 1200 W + V^① 600 W

TECHNICOLOGICAL INFORMATION

Greenor heating & cooling radiator with very high energy efficiency with powder-coated steel frame and covered on the front face with an Olycale® stone plate.

Olycale® stone face: a natural stone from the Pyrenees, crushed and then restructured specifically to emit high performance heat.

More ecological: Copper / aluminum exchanger working with water circulation, without polluting refrigerant as in traditional air conditioners (harmful to global warming).

Very low total power consumption: 10 W on average, 18 W max.

Easy to use: 3 manual or automatic fan speeds.

Very quiet operation, sound power in 1st gear: 14 Dba

No air flow: linear and horizontal air flow at very low speed (0.4 to 1.4 m / s) diffused over a 492 cm perimeter all around a specific steel frame.

CE standards according to Eurovent: EN 60335-2-30, EN 55014-1 (Ed 2006), EN 61000-3-2 (Ed2006) and EN 61000-3-3 / A1 (Ed 1995/01).

